

Wärmepumpe Technische Datenblatt

	THMLd-8D/ 3HBP-A	THMLd-10D/ 3HBp-A	THMLd-12S/ 9HBp-A	THMLd-16S/ 9HBp-A
ERP-Klasse/Etas EN14825 (35 °C)	A +++	A +++	A +++	A +++
ERP-Klasse/Etas EN14825 (55 °C)	A ++	A ++	A ++	A ++
Ausdehnungsgefäß	8 l	9 l	9 l	9 l
Heizleistung (A-7/W35)	8,0 kW	10,0 kW	12,1 kW	15,0 kW
Nenneingangsleistung (A-7/W35)	1,85 kW	2,25 kW	2,42 kW	3,54 kW
COP bei A-7/W35	4,32	4,44	5,0	4,52
SCOP	4,60	4,68	4,77	4,56
Kühlleistung (A-35/W18)	7,5 kW	10,0 kW	12,0 kW	15,0 kW
Nenneingangsleistung (A-35/W18)	2,1 kW	2,8 kW	6,97 kW	4,35 kW
SEER	5,1	5,3	5,0	4,52
Schallleistungspegel	60 dB (A)	61 dB (A)	64 dB (A)	68 dB (A)

Kreislauf				
Kältemittel (GWP)	R32 (675)	R32 (675)	R32 (675)	R32 (675)
Anschlüsse / Gewinde	R5/4"	R5/4"	R5/4"	R5/4"
Schalldruck				
Außen	47 dB(A)	50 dB(A)	53 dB(A)	55 dB(A)
Verbrauch				
Stromversorgung	220-240V~/50 Hz/1P	220-240V~/50 Hz/1P	380-415V~/50 Hz/3P	380-415V~/50H z/3P
Produktmaße				
Maße BxHxT	1293×860×495	1293×860×495	1293×860×495	1293×860×495
Gewicht	112 kg	112 kg	124 kg	124 kg
Energielabel				